

**Hydraulikschläuche - Meterware - 1 SN\***



Arbeitstemperatur: -40°C + 125°C

Artikelnr.	Innen-Ø	Außen-Ø	Max. Arbeitsdruck	Min. Berstdruck
	mm	mm	bar	bar
1SN06	6	13,4	190	759
1SN08	8	15	172	690
1SN10	10	17,4	155	621
1SN12	12	20,6	138	552
1SN16	16	23,7	103	414
1SN20	20	27,7	86	345
1SN25	25	35,6	69	276
1SN32	32	43,5	43	172

**Hydraulikschläuche - Meterware - 2 SN\***



Arbeitstemperatur: -40°C + 125°C

Artikelnr.	Innen-Ø	Außen-Ø	Max. Arbeitsdruck	Min. Berstdruck
	mm	mm	bar	bar
2SN06	6	15	345	1379
2SN08	8	16,6	293	1172
2SN10	10	19	276	1103
2SN12	12	22,2	241	966
2SN16	16	25,4	190	759
2SN20	20	29,3	155	621
2SN25	25	38,1	138	552
2SN32	32	48,3	112	449

**Hydraulikschläuche - Meterware - 4 SP\***



Arbeitstemperatur: -40°C + 125°C

Artikelnr.	Innen-Ø	Außen-Ø	Max. Arbeitsdruck	Min. Berstdruck
	mm	mm	bar	bar
4841000	10	21,4	445	1780
4841300	13	24,6	415	1660
4841600	16	28,5	360	1440
4842000	20	32	350	1400
4842500	25	39,7	290	1160
4843200	32	50,8	210	840